


## PIN OUT



SHELL ———— SHELL

## REQUIREMENTS:

1:100% short and open testing.

2:Test conditions

DC300V /10MS

Insulation resistance 10MΩ(Min)

Conduction resistance 5Ω(Max)

⑤	OUTER MOLDED	BLACK 45P PVC	0.021	KG
④	INTER MOLDED	LDPE	0.008	KG
③	CONNECTOR	USB A TYPE FEMALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
②	CONNECTOR	USB A TYPE MALE,WHITE INSULATOR,NICKEL PLATED SHELL,GOLD PLATED PIN	1	PCS
①	CABLE	USB2.0 28#*1P+28#*2C+ADB OD:3.9±0.1 JACKET:BLACK PVC	1.5	M
NO.	MATERIAL	DESCRIPTIONG	QTY.	UNIT

Ltemref	Quantity	Title/Name,designation,material,dimension etc			Article No./Reference	
Designed by	Checked by	Approved by - date	File name	Date	Scale	
		MARCH 4.2012	USB AM TO AF L=1.5M	MARCH 4.2012	FREE	
				26-2803		
				26-2803	Edition 1	Sheet 1/2